

# AMBERJACK PIPELINE COMPANY LLC

IN CONNECTION WITH

## EMPIRE DEEPWATER LLC

APPLYING ON THE TRANSPORTATION OF

### PETROLEUM

SUBJECT TO THE RULES AND REGULATIONS DEFINED HEREIN

(Rates in cents per Barrel of 42 United States Gallons each)

| <b>ROUTE NO.</b> | <b>ORIGIN</b>  | <b>DESTINATION</b>                                    | <b>CONTRACT RATE <sup>(1)</sup></b> | <b>RATE</b> |
|------------------|--|---|-------------------------------------|-------------|
| 01               | Grand Isle Block 115, Offshore Louisiana originating from Coelacanth leases*     | Fourchon (Mars Pipeline), Lafourche Parish, Louisiana | [I] 246.55                          | [I] 298.60  |
| 02               | Grand Isle Block 115, Offshore Louisiana originating from non-Coelacanth leases* |   | [I] 246.55                          | [I] 298.60  |
| 03               | Grand Isle Block 116, Offshore Louisiana   |   | N/A                                 | [I] 298.60  |
| 04               | South Timbalier Block 231, Offshore Louisiana                                    |   | N/A                                 | [I] 298.60  |
| 05               | Grand Isle Block 115, Offshore Louisiana originating from Coelacanth leases*     | Green Canyon Block 19, Offshore Louisiana             | [I] 246.55                          | [I] 408.60  |
| 06               | Grand Isle Block 115, Offshore Louisiana originating from non-Coelacanth leases* |   | [I] 246.55                          | [I] 408.60  |
| 07               | Grand Isle Block 116, Offshore Louisiana   |   | N/A                                 | [I] 408.60  |
| 08               | South Timbalier Block 231, Offshore Louisiana                                    |   | N/A                                 | [I] 408.60  |
| 09               | Grand Isle Block 115, Offshore Louisiana originating from Coelacanth leases*     | Ship Shoal Block 332-A, Offshore Louisiana            | [I] 246.55                          | [I] 408.60  |
| 10               | Grand Isle Block 115, Offshore Louisiana originating from non-Coelacanth leases* |   | [I] 246.55                          | [I] 408.60  |
| 11               | Grand Isle Block 116, Offshore Louisiana   |   | N/A                                 | [I] 408.60  |
| 12               | South Timbalier Block 231, Offshore Louisiana                                    |   | N/A                                 | [I] 408.60  |

(1) Note: In addition, Amberjack Pipeline will assess a surcharge in accordance with separately entered Dedication contract(s) between Amberjack and its Counterparties for the specified routes in those contracts.

**ROUTE(S):** *Empire Deepwater LLC Block 115, Grand Isle, Offshore Louisiana to Amberjack Pipeline Company LLC Block 162, South Timbalier, Offshore Louisiana. Amberjack Pipeline Company LLC Block 162, South Timbalier to Fourchon (Mars Pipeline), Lafourche Parish, Louisiana.*  
*Empire Deepwater LLC Block 116, Grand Isle, Offshore Louisiana to Amberjack Pipeline Company LLC Block 162, South Timbalier, Offshore Louisiana. Amberjack Pipeline Company LLC Block 162, South Timbalier to Fourchon (Mars Pipeline), Lafourche Parish, Louisiana.*  
*Empire Deepwater LLC Block 231, South Timbalier, Offshore Louisiana to Amberjack Pipeline Company LLC Block 162, South Timbalier, Offshore Louisiana. Amberjack Pipeline Company LLC Block 162, South Timbalier to Fourchon (Mars Pipeline), Lafourche Parish, Louisiana.*

---

\* Coelacanth leases are defined as originating from the following locations - OCS-G 27982 (covering Ewing Bank Block 834), OCS-G 33707 (covering Ewing Bank Block 835), OCS-G 33140 (covering Ewing Bank Block 790), and OCS-G 33177 (covering Mississippi Canyon Block 793). All other origination point barrels would be considered non-Coelacanth for purposes of movement under this transportation sheet.

---

Note associated with Routes 05-12: Due to operational considerations, Amberjack Pipeline will only be able to accept nominations on these routes when barrels nominated upstream of Green Canyon Block 19 to Fourchon are equal to or exceed the total downstream nominations to Green Canyon 19. If the upstream nominations are less than the total downstream nominations, prorationing procedures, as stated in Rule No. 75 and additional considerations referenced in this sheet, will be followed.

---

**EFFECTIVE: JULY 1, 2024**

---

Issued By:  
ANDY STILLEY, President  
AMBERJACK PIPELINE COMPANY LLC  
P.O. Box 2648  
Houston, Texas 77252

Compiled By:  
Charles Hawkins  
Tariff & Compliance Lead  
(832) 762-2775

**EXPLANATION OF REFERENCE MARKS:**

**[I]** Increase  
**[N]** New  
**[U]** Unchanged  
**[W]** Change in wording only

## **RULES AND REGULATIONS**

The Carrier will transport Petroleum as defined herein, receiving and delivering the same through its own facilities and lines, and where applicable, lines of connecting carriers, subject to the following Rules and Regulations:

### **5. DEFINITIONS**

"Barrel" as herein used means forty-two (42) United States gallons at sixty degrees (60°) Fahrenheit and zero (0) gauge pressure if the vapor pressure of the Petroleum is at or below atmospheric pressure, or at equilibrium pressure if the vapor pressure of the Petroleum is above atmospheric pressure.

"Carrier" as herein used means Amberjack Pipeline Company LLC. Where applicable, this singular term may also cover the plural form "Carriers", which includes Empire Deepwater LLC as joint carrier.

"Consignor" as herein used means the party from whom a Shipper has ordered the receipt of Petroleum.

"Consignee" as herein used means the party to whom a Shipper has ordered the delivery of Petroleum.

"Petroleum" as herein used means the direct liquid products of oil wells, or a mixture of the direct liquid products of oil wells with the indirect liquid products of oil and gas wells including gasoline and liquefied petroleum gases.

"Shipper" as herein used means a party who contracts with Carrier for transportation of Petroleum, as defined herein and under the terms of these Rules and Regulations.

"Nomination", or variations thereof, as herein used means an offer by a Shipper to the Carrier of a stated quantity of Petroleum for transportation from a specified origin or origins to a specified destination in accordance with these Rules and Regulations.

### **10. NOMINATION REQUIRED**

Petroleum will be transported by Carrier only under a Nomination accepted by Carrier. Any Shipper desiring to Nominate Petroleum for transportation shall make such Nomination to Carrier prior to 12 Noon Central Standard Time/Central Daylight Saving Time, whichever is applicable, on the twentieth (20th) day of the month preceding the month during which transportation under the Nomination is to begin; except that, if space is available for current movement, Carrier has the right to accept a Nomination of Petroleum for transportation after the twentieth (20th) day of the month preceding the month during which transportation under the Nomination is to begin. When the twentieth (20th) day of the month falls on a weekend or a holiday, Nominations will be required prior to 12 Noon Central Standard Time/Central Daylight Saving Time, whichever is applicable, on the preceding workday.

### **15 MINIMUM NOMINATION**

Nominations for the transportation of Petroleum for which Carrier has facilities will be accepted into Carrier's system under these Rules and Regulations in quantities of not less than ten thousand (10,000) Barrels aggregate from one or more Shippers as operations permit and/or consistent with the minimum volume requirements of outbound pipeline carriers and provided such Petroleum is of similar quality and characteristics as is being transported from receipt point to destination point; except that Carrier reserves the right to accept any quantity of Petroleum from lease tanks or other facilities to which Carrier's facilities are connected if such quantity can be consolidated with other Petroleum such that Carrier can make a single delivery of not less than ten thousand (10,000) Barrels, and Carrier will not be obligated to make any single delivery of less than ten thousand (10,000) Barrels, unless Carrier's operations dictate otherwise. The term "single delivery" as used herein means a delivery of Petroleum in one continuous operation to one or more Consignees into a single facility, furnished by such Consignee or Consignees, to which Carrier is connected.

## **20. TITLE**

The Carrier shall have the right to reject any Petroleum which may be involved in litigation, or the title of which may be in dispute, or which may be encumbered by a lien or charge of any kind, and require satisfactory evidence of Shipper's perfect and unencumbered title or satisfactory indemnity bond to protect Carrier. By Nominating Petroleum, the Shipper warrants and guarantees that the Shipper has unencumbered title thereto or the right to cause the Petroleum to be transported and that unencumbered title or right remains in effect throughout the movement covered by this transportation sheet. In addition, Shipper agrees to hold Carrier harmless for any and all loss, cost, liability, damage or expense resulting from failure of title or Shipper's failure to have the right to cause the Petroleum to be transported; and Shipper agrees that acceptance by the Carrier of the Petroleum for transportation shall not be deemed a representation by the Carrier as to title.

## **25. SHIPMENT QUALITY**

Carrier reserves the right to reject:

- A. Petroleum having a Reid vapor pressure in excess of 8.6.
- B. Petroleum containing water, sediment and other impurities totaling in excess of one percent (1%) as determined by industry accepted tests, or by such other tests as may be agreed upon by the Shipper and Carrier.
- C. Petroleum where the Shipper or Consignee has failed to comply with all applicable laws, rules and regulations made by any governmental authorities regulating shipments of Petroleum.
- D. Petroleum that has been contaminated by the existence of and/or excess amounts of impure substances, including but not limited to chlorinated and/or oxygenated hydrocarbons such as methanol, or arsenic, lead, and/or other metals which cause harm to other Shippers, connecting carriers, users of the contaminated Petroleum or Carrier.
- E. Petroleum where gravity, viscosity, pour point, or other characteristics are such that it is not readily susceptible to transportation through the Carrier's existing facilities.
- F. Petroleum which may materially affect the quality of other shipments or cause disadvantage to other Shippers and/or the Carrier.

Notwithstanding the above, Carrier may accept Petroleum from Shipper that does not meet the above conditions due to, but not limited to, operational circumstances (i.e. offshore deep water well maintenance or production facility upsets), emergencies, or events of force majeure (such as sea storms or shut-in platforms). In such case, however, Shipper must notify Carrier fully, in writing, of the characteristics of such Petroleum and Shipper shall then secure from the producer or connecting carrier or shall provide itself, in writing, to Carrier an assumption of all liability and agree to hold Carrier harmless from and against any loss, cost or disadvantage to other Shippers, and other pipelines or downstream facilities, or to Carrier arising from such transportation.

If Carrier determines that a Shipper has delivered to Carrier's facilities Petroleum that has been contaminated by the existence of and/or excess amounts of impure substances, including but not limited to, chlorinated and/or oxygenated hydrocarbons such as methanol, or arsenic, lead, and/or other metals which cause harm to other Shippers, connecting carriers, users of the contaminated Petroleum or Carrier, such Shipper will be excluded from further entry into applicable segments of the pipeline system until such time as the quality of the Petroleum is to the satisfaction of the Carrier. Carrier is not responsible for monitoring receipts or deliveries for contaminants. Further, Carrier reserves the right to dispose of any contaminated Petroleum blocking its pipeline system. Disposal thereof may be made in any reasonable manner including but not limited to commercial sales, and any liability associated with the contamination or disposal of any Petroleum shall be borne by the Shipper who introduced into Carrier's system such Petroleum that does in any way not comply with the above conditions.

Notwithstanding the foregoing, in general, the Shipper who introduced into Carrier's system Petroleum that does in any way not comply with the above conditions is liable towards Carrier for all consequences of transportation by Carrier of such Petroleum, including but not limited to, damages, costs and expenses of disposal, costs and expenses necessary to return the Carrier's system facilities to service, claims from other Shippers, connecting carriers, or users of the non-complying Petroleum, and the costs of any regulatory or judicial proceeding.

### **30. MIXING OF PETROLEUM IN TRANSIT**

Petroleum will be accepted for transportation only on condition that it may be subject to such changes in gravity or quality while in transit as would result from its mixture with other Petroleum in the pipelines or tanks of the Carrier. Carrier shall not be liable for such changes. Carrier shall be under no obligation to deliver the identical Petroleum received but may make delivery out of common stock or out of Carrier's pipeline stream.

### **40. ADDITIVES**

Carrier reserves the right to require, approve or reject the injection of corrosion inhibitors, viscosity or pour point depressants or other such additives in Petroleum to be transported.

### **45. DUTY OF CARRIER**

Carrier shall transport Petroleum with reasonable diligence, considering the quality of the Petroleum, the distance of transportation, the safety of operation, and other material elements. Carrier can not commit to delivering Petroleum to a particular destination at a particular time.

### **50. ORIGIN FACILITIES REQUIRED FOR AUTOMATIC CUSTODY TRANSFER**

Shipper shall furnish the necessary facilities at origin points capable of delivering Petroleum into the Carrier's system at pressures and pumping rates required and determined solely by the Carrier.

Where Consignor (or Shipper) elects to deliver Petroleum to the Carrier at point of origin through automatic custody transfer facilities (in lieu of tankage), the Consignor (or Shipper) shall furnish the required automatic measuring and sampling facilities and the design, construction, and calibration of such facilities must be approved by the Carrier and any appropriate regulatory body. In the event automatic custody transfer is made by meters, the Consignor (or Shipper) shall also furnish whatever pumping service is necessary to ensure that the Petroleum being delivered to the meter is at a pressure in excess of the bubble point of the liquid.

### **55. DESTINATION FACILITIES REQUIRED**

The Carrier may refuse to accept Petroleum for transportation unless satisfactory written evidence is furnished that the Shipper or Consignee has made the necessary arrangements for shipment beyond or has provided the necessary facilities for receiving said Petroleum as it arrives at the destination. Notwithstanding other conditions, at minimum such facilities shall have adequate available capacity and be capable of receiving said Petroleum at pressures and pumping rates required and determined solely by the Carrier.

### **60. NOTICE OF ARRIVAL, DELIVERY AT DESTINATION**

Delivery may be made upon twenty-four (24) hours notice to the Shipper or Consignee who shall accept and receive said Petroleum from the Carrier with all possible dispatch into the tanks or receptacles to be provided by the Shipper or Consignee.

If the Shipper, or Consignee, is unable or refuses to receive said Petroleum as it arrives at the destination, the Carrier reserves the right to make whatever arrangements for disposition of the Petroleum it deems

appropriate in order to clear its pipeline. Any additional expenses incurred by the Carrier in making such arrangements shall be borne by the Shipper or Consignee.

## **65. INVENTORY REQUIREMENTS**

Prior to delivering Barrels out of Carrier's pipeline system, each Shipper will be required to supply a pro rata share of Petroleum necessary to ensure efficient operation of Carrier's pipeline system. Petroleum provided by Shippers for this purpose may be withdrawn only after:

- (1) Shipments have ceased and the Shipper has notified Carrier in writing of its intention to discontinue shipments in Carrier's system, and
- (2) Shipper balances have been reconciled between Shipper and Carrier.

Carrier, at its discretion, may require advance payment of transportation charges on the volumes to be cleared from Carrier's system, and any unpaid accounts receivable, before final delivery will be made. Carrier shall have a reasonable period of time from the receipt of said notice to complete administrative and operational requirements incidental to Shipper withdrawal.

## **70 GAUGING, TESTING, AND VOLUME CORRECTIONS**

Petroleum shipped hereunder shall be measured and tested by representatives of the Carrier or by automatic equipment approved by the Carrier. Quantities shall be determined by dynamic or static measurement methods in accordance with appropriate American Petroleum Institute (API) standards, latest revision, and adjusted to base (reference or standard) conditions.

The base conditions for the measurement of liquids, such as Petroleum and its liquid products, having a vapor pressure equal to or less than atmospheric pressure at base temperature are as follows:

Pressure . . . . . 14.696 psia (101.325 kPa)  
Temperature . . . . . 60.0 F (15.56 C)

For liquids, such as liquid hydrocarbons, having a vapor pressure greater than atmospheric pressure at base temperature, the base pressure shall be the equilibrium vapor pressure at base temperature.

Deductions will be made for the actual amount of non-merchantable quantities, specifically basic sediment and water and/or other impurities as ascertained by industry accepted test method or other tests agreed upon.

When indirect liquid products are received from pressure vessels using static measurement methods, a further adjustment will be made to cover evacuation losses if a gas blanket at or in excess of the vapor pressure of the liquid is not used.

One of the following pipeline loss allowances will be used when specifically referenced in the transportation sheet.

### Option 4

From the net quantities so determined for acceptance, a further deduction of one-tenth of one percent (0.1%) will be made to cover evaporation and loss during transportation. The balance shall be the net quantities deliverable.

All receipts of Petroleum and indirect liquid products having an API gravity of 45 degrees or above shall also be subject to a deduction to cover the shrinkage and incremental evaporation resulting from the mixture thereof, in Carrier's facilities, with Petroleum having an API gravity of 44.9 degrees or less. Such deduction shall be determined in accordance with the following table:

| <u>API Gravity, Degrees</u> | <u>Deduction for Incremental Evaporation &amp; Shrinkage</u> |
|-----------------------------|--|
| 45 through 54.9             | 0.50%  |
| 55 through 64.9             | 1.00%  |
| 65 through 74.9             | 1.50%  |
| 75 and above                | 2.00%  |

After consideration of all of the factors set forth in this Item No. 70, a net balance will be determined as the quantity deliverable by Carrier, and transportation charges will be assessed on this net balance.

## **75. APPORTIONMENT WHEN NOMINATIONS ARE IN EXCESS OF FACILITIES**

At such times as Carrier determines that it may be necessary to allocate space in a pipeline segment, the transportation furnished by Carrier shall be apportioned among "Regular Shippers" and "New Shippers" as follows:

### (1) Apportionment Definitions:

- a. The "Base Period" is a period of 12 months beginning 13 months prior to the month of allocation and excluding the month preceding the month of allocation.
- b. A "Regular Shipper" is any Shipper having a record of movement(s), in the line segment being prorated, during the Base Period and does not meet the definition of a New Shipper.
- c. A "New Shipper" is any Shipper having no record of movement(s), in the line segment being prorated, during the Base Period. A New Shipper shall not become a Regular Shipper until the beginning month of the defined Base Period for the requested shipment month equals the Shipper's first month of physical movement. For ease in interpreting this definition, the following example illustrates the intent:

| <b>Shipper Nominates for and moves barrels in January 2013 for its first movement on the pipeline system.</b>  |   |                       |
|--|---|-----------------------|
| <b>Shipper will not become a Regular Shipper until February 2014 as shown in the table below. February 2014 would be the month where a defined Base Period would set January 2013 as the first month of its Base Period.</b> |   |                       |
| <b>Calendar Month</b>  | <b>Base Period Definition for February 2014</b> | <b>Shipper Status</b> |
| Jan-13   | Base Period Month 1                             | New                   |
| Feb-13   | Base Period Month 2                             | New                   |
| Mar-13   | Base Period Month 3                             | New                   |
| Apr-13   | Base Period Month 4                             | New                   |
| May-13   | Base Period Month 5                             | New                   |
| Jun-13   | Base Period Month 6                             | New                   |
| Jul-13   | Base Period Month 7                             | New                   |
| Aug-13   | Base Period Month 8                             | New                   |
| Sep-13   | Base Period Month 9                             | New                   |
| Oct-13   | Base Period Month 10                            | New                   |
| Nov-13   | Base Period Month 11                            | New                   |
| Dec-13   | Base Period Month 12                            | New                   |
| Jan-14   | Excluded month                                  | New                   |
| Feb-14   | Allocated Month                                 | Regular               |

(2) New Shippers shall be initially allocated up to a total of ten percent (10%) of the available pipeline capacity. If more than one New Shipper has Nominated volumes, pipeline space shall be allocated proportionately to each New Shipper in relation to the total Nominations by New Shippers, so that the total pipeline capacity allocated for all New Shippers shall not exceed ten percent (10%) of the

available pipeline capacity unless Item (3) re-allocates unused space previously reserved for Regular Shippers.

(3) The remaining capacity shall be allocated among Nominating Regular Shippers as the lesser value of either the Shipper's proportion of the Regular Shippers' Base Period shipment volume or the Shipper's Nominated volume. If a Regular Shipper Nominates less than their calculated allocation, the unused space will be allocated to other Regular Shippers as described in this item. Should the sum of Nominations submitted by all Regular Shippers be less than ninety percent (90%), any unused space will be offered to New Shippers in accordance with the procedures stated in Item (2) of this section.

No Nominations shall be considered beyond the amount which the party requesting shipment has available for shipment. Carrier reserves the right to require Shipper to show sufficient evidence of available volume.

#### **80. APPLICATION OF RATES & CHARGES**

Petroleum accepted for transportation shall be subject to the rates and charges in effect on the date of receipt of such Petroleum by the Carrier. Trunk line transportation and all other lawful charges will be collected on the basis of the net quantities of Petroleum delivered. All net quantities will be determined in the manner provided in Item 70 (GAUGING, TESTING, AND VOLUME CORRECTIONS).

#### **85 APPLICATION OF RATES FROM AND TO INTERMEDIATE POINTS**

For Petroleum accepted for transportation from any point on Carrier's lines not named in a particular transportation sheet, which is intermediate to a point from which rates are published in said transportation sheet, through such unnamed point, the rate published from the next more distant point specified in such transportation sheet will apply.

For Petroleum accepted for transportation to any point not named in a particular transportation sheet which is intermediate to a point to which rates are published in said transportation sheet, through such unnamed point, the rate published therein to the next more distant point specified in the transportation sheet will apply.

#### **95. COMMODITY**

The Carrier will transport Petroleum and has no obligation to accept any other commodity for transportation.

#### **100. PAYMENT OF TRANSPORTATION AND OTHER CHARGES**

Shipper shall be responsible for payment of transportation and all other charges applicable to the shipment, and Carrier shall have the right to require Shipper to prepay such charges or furnish guaranty of payment satisfactory to Carrier. Petroleum accepted for transportation shall be subject to the rates in effect on the date of receipt by Carrier, irrespective of the date of the Nomination.

Except where pre-payment is required, all charges shall be paid by Shipper within ten (10) days from the date of invoice from Carrier. All charges that remain unpaid for more than ten (10) days from the date of Carrier's invoice shall accrue an interest charge equal to 125% of the prime rate as quoted by a major New York bank or the maximum non-usurious interest rate that may then be charged under applicable law.

Carrier shall have a lien on all Petroleum accepted for transportation to secure payment of all charges, including demurrage charges, and may refuse to accept future Nominations and/or make delivery of any Petroleum until all charges have been paid. If such charges, or any part thereof, remain unpaid five (5) days after notice and demand therefor or when there shall be failure to take the Petroleum at the point of destination within five (5) days per Item 60 (NOTICE OF ARRIVAL, DELIVERY AT DESTINATION) of these Rules and Regulations, the Carrier, or its representatives, shall have the right to sell such Petroleum. The Carrier may be a bidder and purchaser at such sale. From the proceeds of the sale, the Carrier may deduct all charges lawfully accruing, including demurrage, and all expenses of the sale. The net balance shall be held without interest for whomsoever may be lawfully entitled thereto.



In addition to all other charges accruing on Petroleum accepted for transportation through Carrier's facilities, a per Barrel charge will be assessed and collected in the amount of any fee or other charge, however denominated, which is levied against Carrier by any federal, state or local agency.

#### **105. DIVERSION**

Subject to Item 15 (MINIMUM NOMINATION), change in destination or routing will be permitted without additional charge, on written request from the Shipper, provided an applicable transportation sheet is in effect for any requested destination or routing, and provided that no back-haul is required.

#### **110. LIABILITY OF CARRIER**

As a condition to Carrier's acceptance of Petroleum, each Shipper agrees that Carrier shall not be liable for any loss thereof, damage thereto, or delay, except to the extent that liability therefor is imposed on the Carrier by law. In case of loss of or damage to Petroleum for which Carrier is not responsible under applicable law, the Shipper shall bear the loss or damage in such proportion as its total volume in Carrier's Pipeline System bears to the total volume in said system.

If Carrier is unable to accept Petroleum for any reason, Carrier will not be liable for delay or damages associated with its inability to accept volumes.

#### **115. CLAIMS, SUITS, AND TIME FOR FILING**

As a condition precedent to recovery for loss, damage, or delay to shipments, claims must be filed in writing with the Carrier within nine (9) months after delivery of the Petroleum, or, in case of failure to make delivery, then within nine (9) months after a reasonable time for delivery has elapsed; and suits arising out of such claims shall be instituted against the Carrier only within two (2) years from the time when the Carrier delivers, or arranges delivery of, the Petroleum or, in case of failure to make or arrange delivery, then within two (2) years after a reasonable time for delivery has elapsed. Any such loss or damage shall be determined solely on the basis of volumetric loss and not on the monetary value of the Petroleum. Where claims are not filed or suits are not instituted thereon in accordance with the foregoing provisions, Carrier will not be liable and such claims will not be paid.

#### **120. PIPEAGE OR OTHER CONTRACTS**

Separate pipeage and other contracts may be required of a Shipper, in accordance with the applicable transportation sheet and these Rules and Regulations, before any duty of transportation by the Carrier shall arise.

#### **125. QUALITY BANK**

To assure that no Shipper will be materially damaged or allowed to benefit by changes in gravity and sulfur due to the intermixing of Petroleum in the system, Shippers will be required, as a condition of Nominating, to participate in a Gravity and Sulfur Bank. A fee of **[U]** 0.5 cents per Barrel will be assessed to cover costs for administration of the quality bank for the Shippers.

The tables of gravity and sulfur differential values per Barrel as attached hereto as Exhibits A, B, and C are incorporated herein and made a part of these Rules and Regulations.

Carrier shall administer the quality bank providing adjustments for the value of Petroleum with different qualities in the manner specified below for both receipt and delivery volumes:

Applicable Barrels and gravities shall be the net Barrels at 60 degrees Fahrenheit (with no deduction for loss allowance) and the gravities recorded by the Carrier at points where it customarily records gravities and quantities.

The weighted average gravity differential value per Barrel (for two or more gravities of Petroleum), as hereinafter referred to, shall be obtained in the following manner: multiply the gravity differential values per Barrel (from the attached tables as same are from time to time revised) by the number of Barrels to which such gravity differential values are applicable and then divide the total of the resultant gravity differential values in dollars and cents by the total of the applicable Barrels.

Applicable Barrels and sulfur content shall be the net Barrels at 60 degrees Fahrenheit (with no deduction for loss allowance) and the sulfur content recorded by a competent laboratory for samples obtained by the Carrier at the points where it customarily measures and samples receipts for custody transfer.

The weighted average sulfur differential value per Barrel (for two or more sulfur contents of Petroleum), as hereinafter referred to, shall be obtained in the following manner: multiply the sulfur differential values per Barrel by the number of Barrels to which such sulfur differential values are applicable and then divide the total of the resultant sulfur differential values in dollars and cents by the total of the applicable Barrels.

Sulfur content as furnished by the laboratory at the true gravity shall be adjusted to reflect its comparison to the reference Petroleum at 35.5 degree gravity. The adjustment to the test sulfur content shall be made by establishing a ratio of weight per gallon for the gravity of the sample to weight per gallon for the gravity of the reference Petroleum of 35.5 degree gravity. The Table of Ratio Factors for Sulfur Adjustments is attached hereto as Exhibit "C" and is made a part of these Rules and Regulations.

The ratio thus obtained will be applied against the tested sulfur content of the sample to obtain the adjusted sulfur content (gravity ratio x tested sulfur content = adjusted sulfur content). The adjusted sulfur content will then be used to obtain the sulfur differential value per Barrel from the table of sulfur differential values per Barrel (Exhibit "B").

I. Adjustment between Shippers, for both receipt volumes and delivery volumes, shall be computed as follows:

A. Compute the weighted average gravity differential value per Barrel of the Barrels received from/delivered to each Shipper.

B. Compute the weighted average sulfur differential value per Barrel of the Barrels received from/delivered to each Shipper. Sulfur differential values from 0 to 0.75 will be considered 0.75.

II. Compute the weighted average gravity differential value per Barrel of the composite common stream for receipts and deliveries.

*Receipt Calculation:*

A. If the weighted average gravity differential value per Barrel of a Shipper as so determined under Paragraph I above shall be greater than the weighted average gravity differential value per Barrel of the aforementioned common stream Petroleum as determined under Paragraph II, the difference in cents per Barrel shall be calculated and Shipper shall be credited (receives from the bank) an amount calculated by multiplying said difference in gravity differential value per Barrel by the applicable Barrels.

B. If the weighted average gravity differential value per Barrel of a Shipper is less than the weighted average gravity differential value per Barrel of the aforementioned common stream Petroleum, the difference shall be calculated as above outlined and a Shipper debited (pays to the bank) for such difference.

*Delivery Calculation:*

A. If the weighted average gravity differential value per Barrel of a Shipper as so determined under Paragraph I above shall be greater than the weighted average gravity differential value per Barrel of the aforementioned common stream Petroleum as determined under Paragraph II, the difference in cents per Barrel shall be calculated and Shipper shall be debited (pays the bank) an amount calculated by multiplying said difference in gravity differential value per Barrel by the applicable Barrels.

B. If the weighted average gravity differential value per Barrel of a Shipper is less than the weighted average gravity differential value per Barrel of the aforementioned common stream Petroleum, the difference shall be calculated as above outlined and a Shipper credited (receives from the bank) for such difference.

III. Compute the weighted average sulfur differential value per Barrel of the composite common stream for receipts and deliveries

*Receipt Calculation:*

A. If the weighted average sulfur differential value per Barrel of a Shipper as so determined under Paragraph I above shall be greater than the weighted average sulfur differential value per Barrel of the aforementioned common stream Petroleum as determined under Paragraph III, the difference in cents per Barrel shall be calculated and Shipper shall be debited (pays the bank) an amount calculated by multiplying said difference in sulfur differential value per Barrel by the applicable Barrels.

B. If the weighted average sulfur differential value per Barrel of a Shipper is less than the weighted average sulfur differential value per Barrel of the aforementioned common stream Petroleum, the difference shall be calculated as above outlined and Shipper shall be credited (receives from the bank) for such difference.

*Delivery Calculation:*

A. If the weighted average sulfur differential value per Barrel of a Shipper as so determined under Paragraph I above shall be greater than the weighted average sulfur differential value per Barrel of the aforementioned common stream Petroleum as determined under Paragraph III, the difference in cents per Barrel shall be calculated and Shipper shall be credited (receives from the bank) an amount calculated by multiplying said difference in sulfur differential value per Barrel by the applicable Barrels.

B. If the weighted average sulfur differential value per Barrel of a Shipper is less than the weighted average sulfur differential value per Barrel of the aforementioned common stream Petroleum, the difference shall be calculated as above outlined and Shipper shall be debited (pays the bank) for such difference.

A sample calculation is attached as Exhibit "D".

These calculations shall be made for each calendar month and the algebraic sum of the adjustments for the system shall be zero  $\pm$  One Dollar. If a Shipper shall have a net debit balance when netting the two adjustments made on receipts and deliveries above, the balance shall be remitted to the clearinghouse within fifteen (15) days from receipt of statement of such debit. If Shipper shall have a credit, the clearinghouse shall remit the amount thereof after receipt by the clearinghouse of the sums from those Shippers having debits as calculated above.

**EXHIBIT "A"**

**ADJUSTMENT AUTHORIZATION**

TABLES OF DIFFERENTIALS FOR USE IN DETERMINING ADJUSTMENTS FOR  
DIFFERENCE IN GRAVITY OF PETROLEUM IN  
CARRIER SYSTEM COMMON STREAM PETROLEUM

| <u>API</u><br><u>GRAVITY</u> | <u>DIFF</u><br><u>PER BBL</u> | <u>API</u><br><u>GRAVITY</u> | <u>DIFF</u><br><u>PER BBL</u> | <u>API</u><br><u>GRAVITY</u> | <u>DIFF</u><br><u>PER BBL</u> | <u>API</u><br><u>GRAVITY</u> | <u>DIFF</u><br><u>PER BBL</u> |
|------------------------------|-------------------------------|------------------------------|-------------------------------|------------------------------|-------------------------------|------------------------------|-------------------------------|
| 20.0                         | 2.750                         | 26.0                         | 3.650                         | 32.0                         | 4.550                         | 38.0                         | 5.060                         |
| 20.1                         | 2.765                         | 26.1                         | 3.665                         | 32.1                         | 4.565                         | 38.1                         | 5.060                         |
| 20.2                         | 2.780                         | 26.2                         | 3.680                         | 32.2                         | 4.580                         | 38.2                         | 5.060                         |
| 20.3                         | 2.795                         | 26.3                         | 3.695                         | 32.3                         | 4.595                         | 38.3                         | 5.060                         |
| 20.4                         | 2.810                         | 26.4                         | 3.710                         | 32.4                         | 4.610                         | 38.4                         | 5.060                         |
| 20.5                         | 2.825                         | 26.5                         | 3.725                         | 32.5                         | 4.625                         | 38.5                         | 5.060                         |
| 20.6                         | 2.840                         | 26.6                         | 3.740                         | 32.6                         | 4.640                         | 38.6                         | 5.060                         |
| 20.7                         | 2.855                         | 26.7                         | 3.755                         | 32.7                         | 4.655                         | 38.7                         | 5.060                         |
| 20.8                         | 2.870                         | 26.8                         | 3.770                         | 32.8                         | 4.670                         | 38.8                         | 5.060                         |
| 20.9                         | 2.885                         | 26.9                         | 3.785                         | 32.9                         | 4.685                         | 38.9                         | 5.060                         |
| 21.0                         | 2.900                         | 27.0                         | 3.800                         | 33.0                         | 4.700                         | 39.0                         | 5.080                         |
| 21.1                         | 2.915                         | 27.1                         | 3.815                         | 33.1                         | 4.715                         | 39.1                         | 5.080                         |
| 21.2                         | 2.930                         | 27.2                         | 3.830                         | 33.2                         | 4.730                         | 39.2                         | 5.080                         |
| 21.3                         | 2.945                         | 27.3                         | 3.845                         | 33.3                         | 4.745                         | 39.3                         | 5.080                         |
| 21.4                         | 2.960                         | 27.4                         | 3.860                         | 33.4                         | 4.760                         | 39.4                         | 5.080                         |
| 21.5                         | 2.975                         | 27.5                         | 3.875                         | 33.5                         | 4.775                         | 39.5                         | 5.080                         |
| 21.6                         | 2.990                         | 27.6                         | 3.890                         | 33.6                         | 4.790                         | 39.6                         | 5.080                         |
| 21.7                         | 3.005                         | 27.7                         | 3.905                         | 33.7                         | 4.805                         | 39.7                         | 5.080                         |
| 21.8                         | 3.020                         | 27.8                         | 3.920                         | 33.8                         | 4.820                         | 39.8                         | 5.080                         |
| 21.9                         | 3.035                         | 27.9                         | 3.935                         | 33.9                         | 4.835                         | 39.9                         | 5.080                         |
| 22.0                         | 3.050                         | 28.0                         | 3.950                         | 34.0                         | 4.850                         | 40.0                         | 5.100                         |
| 22.1                         | 3.065                         | 28.1                         | 3.965                         | 34.1                         | 4.865                         | 40.1                         | 5.100                         |
| 22.2                         | 3.080                         | 28.2                         | 3.980                         | 34.2                         | 4.880                         | 40.2                         | 5.100                         |
| 22.3                         | 3.095                         | 28.3                         | 3.995                         | 34.3                         | 4.895                         | 40.3                         | 5.100                         |
| 22.4                         | 3.110                         | 28.4                         | 4.010                         | 34.4                         | 4.910                         | 40.4                         | 5.100                         |
| 22.5                         | 3.125                         | 28.5                         | 4.025                         | 34.5                         | 4.925                         | 40.5                         | 5.100                         |
| 22.6                         | 3.140                         | 28.6                         | 4.040                         | 34.6                         | 4.940                         | 40.6                         | 5.100                         |
| 22.7                         | 3.155                         | 28.7                         | 4.055                         | 34.7                         | 4.955                         | 40.7                         | 5.100                         |
| 22.8                         | 3.170                         | 28.8                         | 4.070                         | 34.8                         | 4.970                         | 40.8                         | 5.100                         |
| 22.9                         | 3.185                         | 28.9                         | 4.085                         | 34.9                         | 4.985                         | 40.9                         | 5.100                         |
| 23.0                         | 3.200                         | 29.0                         | 4.100                         | 35.0                         | 5.000                         | 41.0                         | 5.100                         |
| 23.1                         | 3.215                         | 29.1                         | 4.115                         | 35.1                         | 5.000                         | 41.1                         | 5.100                         |
| 23.2                         | 3.230                         | 29.2                         | 4.130                         | 35.2                         | 5.000                         | 41.2                         | 5.100                         |
| 23.3                         | 3.245                         | 29.3                         | 4.145                         | 35.3                         | 5.000                         | 41.3                         | 5.100                         |
| 23.4                         | 3.260                         | 29.4                         | 4.160                         | 35.4                         | 5.000                         | 41.4                         | 5.100                         |
| 23.5                         | 3.275                         | 29.5                         | 4.175                         | 35.5                         | 5.000                         | 41.5                         | 5.100                         |
| 23.6                         | 3.290                         | 29.6                         | 4.190                         | 35.6                         | 5.000                         | 41.6                         | 5.100                         |
| 23.7                         | 3.305                         | 29.7                         | 4.205                         | 35.7                         | 5.000                         | 41.7                         | 5.100                         |
| 23.8                         | 3.320                         | 29.8                         | 4.220                         | 35.8                         | 5.000                         | 41.8                         | 5.100                         |
| 23.9                         | 3.335                         | 29.9                         | 4.235                         | 35.9                         | 5.000                         | 41.9                         | 5.100                         |
| 24.0                         | 3.350                         | 30.0                         | 4.250                         | 36.0                         | 5.020                         | 42.0                         | 5.100                         |
| 24.1                         | 3.365                         | 30.1                         | 4.265                         | 36.1                         | 5.020                         | 42.1                         | 5.100                         |
| 24.2                         | 3.380                         | 30.2                         | 4.280                         | 36.2                         | 5.020                         | 42.2                         | 5.100                         |
| 24.3                         | 3.395                         | 30.3                         | 4.295                         | 36.3                         | 5.020                         | 42.3                         | 5.100                         |
| 24.4                         | 3.410                         | 30.4                         | 4.310                         | 36.4                         | 5.020                         | 42.4                         | 5.100                         |
| 24.5                         | 3.425                         | 30.5                         | 4.325                         | 36.5                         | 5.020                         | 42.5                         | 5.100                         |
| 24.6                         | 3.440                         | 30.6                         | 4.340                         | 36.6                         | 5.020                         | 42.6                         | 5.100                         |
| 24.7                         | 3.455                         | 30.7                         | 4.355                         | 36.7                         | 5.020                         | 42.7                         | 5.100                         |
| 24.8                         | 3.470                         | 30.8                         | 4.370                         | 36.8                         | 5.020                         | 42.8                         | 5.100                         |
| 24.9                         | 3.485                         | 30.9                         | 4.385                         | 36.9                         | 5.020                         | 42.9                         | 5.100                         |
| 25.0                         | 3.500                         | 31.0                         | 4.400                         | 37.0                         | 5.040                         | 43.0                         | 5.100                         |
| 25.1                         | 3.515                         | 31.1                         | 4.415                         | 37.1                         | 5.040                         | 43.1                         | 5.100                         |
| 25.2                         | 3.530                         | 31.2                         | 4.430                         | 37.2                         | 5.040                         | 43.2                         | 5.100                         |
| 25.3                         | 3.545                         | 31.3                         | 4.445                         | 37.3                         | 5.040                         | 43.3                         | 5.100                         |
| 25.4                         | 3.560                         | 31.4                         | 4.460                         | 37.4                         | 5.040                         | 43.4                         | 5.100                         |
| 25.5                         | 3.575                         | 31.5                         | 4.475                         | 37.5                         | 5.040                         | 43.5                         | 5.100                         |
| 25.6                         | 3.590                         | 31.6                         | 4.490                         | 37.6                         | 5.040                         | 43.6                         | 5.100                         |
| 25.7                         | 3.605                         | 31.7                         | 4.505                         | 37.7                         | 5.040                         | 43.7                         | 5.100                         |
| 25.8                         | 3.620                         | 31.8                         | 4.520                         | 37.8                         | 5.040                         | 43.8                         | 5.100                         |
| 25.9                         | 3.635                         | 31.9                         | 4.535                         | 37.9                         | 5.040                         | 43.9                         | 5.100                         |

**EXHIBIT "A" CONTINUED**  
**ADJUSTMENT AUTHORIZATION**

TABLES OF DIFFERENTIALS FOR USE IN DETERMINING ADJUSTMENTS FOR  
DIFFERENCE IN GRAVITY OF PETROLEUM IN  
CARRIER SYSTEM COMMON STREAM PETROLEUM

| <u>API</u><br><u>GRAVITY</u> | <u>DIFF</u><br><u>PER BBL</u> | <u>API</u><br><u>GRAVITY</u> | <u>DIFF</u><br><u>PER BBL</u> |
|------------------------------|-------------------------------|------------------------------|-------------------------------|
| 44.0                         | 5.100                         | 50.0                         | 4.350                         |
| 44.1                         | 5.100                         | 50.1                         | 4.335                         |
| 44.2                         | 5.100                         | 50.2                         | 4.320                         |
| 44.3                         | 5.100                         | 50.3                         | 4.305                         |
| 44.4                         | 5.100                         | 50.4                         | 4.290                         |
| 44.5                         | 5.100                         | 50.5                         | 4.275                         |
| 44.6                         | 5.100                         | 50.6                         | 4.260                         |
| 44.7                         | 5.100                         | 50.7                         | 4.245                         |
| 44.8                         | 5.100                         | 50.8                         | 4.230                         |
| 44.9                         | 5.100                         | 50.9                         | 4.215                         |
| 45.0                         | 5.100                         | 51.0                         | 4.200                         |
| 45.1                         | 5.085                         | 51.1                         | 4.185                         |
| 45.2                         | 5.070                         | 51.2                         | 4.170                         |
| 45.3                         | 5.055                         | 51.3                         | 4.155                         |
| 45.4                         | 5.040                         | 51.4                         | 4.140                         |
| 45.5                         | 5.025                         | 51.5                         | 4.125                         |
| 45.6                         | 5.010                         | 51.6                         | 4.110                         |
| 45.7                         | 4.995                         | 51.7                         | 4.095                         |
| 45.8                         | 4.980                         | 51.8                         | 4.080                         |
| 45.9                         | 4.965                         | 51.9                         | 4.065                         |
| 46.0                         | 4.950                         | 52.0                         | 4.050                         |
| 46.1                         | 4.935                         | 52.1                         | 4.035                         |
| 46.2                         | 4.920                         | 52.2                         | 4.020                         |
| 46.3                         | 4.905                         | 52.3                         | 4.005                         |
| 46.4                         | 4.890                         | 52.4                         | 3.990                         |
| 46.5                         | 4.875                         | 52.5                         | 3.975                         |
| 46.6                         | 4.860                         | 52.6                         | 3.960                         |
| 46.7                         | 4.845                         | 52.7                         | 3.945                         |
| 46.8                         | 4.830                         | 52.8                         | 3.930                         |
| 46.9                         | 4.815                         | 52.9                         | 3.915                         |
| 47.0                         | 4.800                         | 53.0                         | 3.900                         |
| 47.1                         | 4.785                         | 53.1                         | 3.885                         |
| 47.2                         | 4.770                         | 53.2                         | 3.870                         |
| 47.3                         | 4.755                         | 53.3                         | 3.855                         |
| 47.4                         | 4.740                         | 53.4                         | 3.840                         |
| 47.5                         | 4.725                         | 53.5                         | 3.825                         |
| 47.6                         | 4.710                         | 53.6                         | 3.810                         |
| 47.7                         | 4.695                         | 53.7                         | 3.795                         |
| 47.8                         | 4.680                         | 53.8                         | 3.780                         |
| 47.9                         | 4.665                         | 53.9                         | 3.765                         |
| 48.0                         | 4.650                         | 54.0                         | 3.750                         |
| 48.1                         | 4.635                         | 54.1                         | 3.735                         |
| 48.2                         | 4.620                         | 54.2                         | 3.720                         |
| 48.3                         | 4.605                         | 54.3                         | 3.705                         |
| 48.4                         | 4.590                         | 54.4                         | 3.690                         |
| 48.5                         | 4.575                         | 54.5                         | 3.675                         |
| 48.6                         | 4.560                         | 54.6                         | 3.660                         |
| 48.7                         | 4.545                         | 54.7                         | 3.645                         |
| 48.8                         | 4.530                         | 54.8                         | 3.630                         |
| 48.9                         | 4.515                         | 54.9                         | 3.615                         |
| 49.0                         | 4.500                         | 55.0                         | 3.600                         |
| 49.1                         | 4.485                         |                              |                               |
| 49.2                         | 4.470                         |                              |                               |
| 49.3                         | 4.455                         |                              |                               |
| 49.4                         | 4.440                         |                              |                               |
| 49.5                         | 4.425                         |                              |                               |
| 49.6                         | 4.410                         |                              |                               |
| 49.7                         | 4.395                         |                              |                               |
| 49.8                         | 4.380                         |                              |                               |
| 49.9                         | 4.365                         |                              |                               |

For API GRAVITY values  
above 55.0° API, the  
differential continues to  
decline .015/bbl per 0.1°  
API GRAVITY

**EXHIBIT "B"**

**ADJUSTMENT AUTHORIZATION**

TABLES OF DIFFERENTIALS FOR USE IN DETERMINING ADJUSTMENTS FOR  
DIFFERENCE IN SULFUR CONTENT OF PETROLEUM IN  
CARRIER SYSTEM COMMON STREAM PETROLEUM

| <u>PERCENT</u><br><u>SULFUR</u> | <u>DIFF</u><br><u>PER BBL</u> | <u>PERCENT</u><br><u>SULFUR</u> | <u>DIFF</u><br><u>PER BBL</u> | <u>PERCENT</u><br><u>SULFUR</u> | <u>DIFF</u><br><u>PER BBL</u> | <u>PERCENT</u><br><u>SULFUR</u> | <u>DIFF</u><br><u>PER BBL</u> |
|---------------------------------|-------------------------------|---------------------------------|-------------------------------|---------------------------------|-------------------------------|---------------------------------|-------------------------------|
| 0.75                            | 1.750                         | 1.35                            | 2.350                         | 1.95                            | 2.950                         | 2.55                            | 3.550                         |
| 0.76                            | 1.760                         | 1.36                            | 2.360                         | 1.96                            | 2.960                         | 2.56                            | 3.560                         |
| 0.77                            | 1.770                         | 1.37                            | 2.370                         | 1.97                            | 2.970                         | 2.57                            | 3.570                         |
| 0.78                            | 1.780                         | 1.38                            | 2.380                         | 1.98                            | 2.980                         | 2.58                            | 3.580                         |
| 0.79                            | 1.790                         | 1.39                            | 2.390                         | 1.99                            | 2.990                         | 2.59                            | 3.590                         |
| 0.80                            | 1.800                         | 1.40                            | 2.400                         | 2.00                            | 3.000                         | 2.60                            | 3.600                         |
| 0.81                            | 1.810                         | 1.41                            | 2.410                         | 2.01                            | 3.010                         | 2.61                            | 3.610                         |
| 0.82                            | 1.820                         | 1.42                            | 2.420                         | 2.02                            | 3.020                         | 2.62                            | 3.620                         |
| 0.83                            | 1.830                         | 1.43                            | 2.430                         | 2.03                            | 3.030                         | 2.63                            | 3.630                         |
| 0.84                            | 1.840                         | 1.44                            | 2.440                         | 2.04                            | 3.040                         | 2.64                            | 3.640                         |
| 0.85                            | 1.850                         | 1.45                            | 2.450                         | 2.05                            | 3.050                         | 2.65                            | 3.650                         |
| 0.86                            | 1.860                         | 1.46                            | 2.460                         | 2.06                            | 3.060                         | 2.66                            | 3.660                         |
| 0.87                            | 1.870                         | 1.47                            | 2.470                         | 2.07                            | 3.070                         | 2.67                            | 3.670                         |
| 0.88                            | 1.880                         | 1.48                            | 2.480                         | 2.08                            | 3.080                         | 2.68                            | 3.680                         |
| 0.89                            | 1.890                         | 1.49                            | 2.490                         | 2.09                            | 3.090                         | 2.69                            | 3.690                         |
| 0.90                            | 1.900                         | 1.50                            | 2.500                         | 2.10                            | 3.100                         | 2.70                            | 3.700                         |
| 0.91                            | 1.910                         | 1.51                            | 2.510                         | 2.11                            | 3.110                         | 2.71                            | 3.710                         |
| 0.92                            | 1.920                         | 1.52                            | 2.520                         | 2.12                            | 3.120                         | 2.72                            | 3.720                         |
| 0.93                            | 1.930                         | 1.53                            | 2.530                         | 2.13                            | 3.130                         | 2.73                            | 3.730                         |
| 0.94                            | 1.940                         | 1.54                            | 2.540                         | 2.14                            | 3.140                         | 2.74                            | 3.740                         |
| 0.95                            | 1.950                         | 1.55                            | 2.550                         | 2.15                            | 3.150                         | 2.75                            | 3.750                         |
| 0.96                            | 1.960                         | 1.56                            | 2.560                         | 2.16                            | 3.160                         | 2.76                            | 3.760                         |
| 0.97                            | 1.970                         | 1.57                            | 2.570                         | 2.17                            | 3.170                         | 2.77                            | 3.770                         |
| 0.98                            | 1.980                         | 1.58                            | 2.580                         | 2.18                            | 3.180                         | 2.78                            | 3.780                         |
| 0.99                            | 1.990                         | 1.59                            | 2.590                         | 2.19                            | 3.190                         | 2.79                            | 3.790                         |
| 1.00                            | 2.000                         | 1.60                            | 2.600                         | 2.20                            | 3.200                         | 2.80                            | 3.800                         |
| 1.01                            | 2.010                         | 1.61                            | 2.610                         | 2.21                            | 3.210                         | 2.81                            | 3.810                         |
| 1.02                            | 2.020                         | 1.62                            | 2.620                         | 2.22                            | 3.220                         | 2.82                            | 3.820                         |
| 1.03                            | 2.030                         | 1.63                            | 2.630                         | 2.23                            | 3.230                         | 2.83                            | 3.830                         |
| 1.04                            | 2.040                         | 1.64                            | 2.640                         | 2.24                            | 3.240                         | 2.84                            | 3.840                         |
| 1.05                            | 2.050                         | 1.65                            | 2.650                         | 2.25                            | 3.250                         | 2.85                            | 3.850                         |
| 1.06                            | 2.060                         | 1.66                            | 2.660                         | 2.26                            | 3.260                         | 2.86                            | 3.860                         |
| 1.07                            | 2.070                         | 1.67                            | 2.670                         | 2.27                            | 3.270                         | 2.87                            | 3.870                         |
| 1.08                            | 2.080                         | 1.68                            | 2.680                         | 2.28                            | 3.280                         | 2.88                            | 3.880                         |
| 1.09                            | 2.090                         | 1.69                            | 2.690                         | 2.29                            | 3.290                         | 2.89                            | 3.890                         |
| 1.10                            | 2.100                         | 1.70                            | 2.700                         | 2.30                            | 3.300                         | 2.90                            | 3.900                         |
| 1.11                            | 2.110                         | 1.71                            | 2.710                         | 2.31                            | 3.310                         | 2.91                            | 3.910                         |
| 1.12                            | 2.120                         | 1.72                            | 2.720                         | 2.32                            | 3.320                         | 2.92                            | 3.920                         |
| 1.13                            | 2.130                         | 1.73                            | 2.730                         | 2.33                            | 3.330                         | 2.93                            | 3.930                         |
| 1.14                            | 2.140                         | 1.74                            | 2.740                         | 2.34                            | 3.340                         | 2.94                            | 3.940                         |
| 1.15                            | 2.150                         | 1.75                            | 2.750                         | 2.35                            | 3.350                         | 2.95                            | 3.950                         |
| 1.16                            | 2.160                         | 1.76                            | 2.760                         | 2.36                            | 3.360                         | 2.96                            | 3.960                         |
| 1.17                            | 2.170                         | 1.77                            | 2.770                         | 2.37                            | 3.370                         | 2.97                            | 3.970                         |
| 1.18                            | 2.180                         | 1.78                            | 2.780                         | 2.38                            | 3.380                         | 2.98                            | 3.980                         |
| 1.19                            | 2.190                         | 1.79                            | 2.790                         | 2.39                            | 3.390                         | 2.99                            | 3.990                         |
| 1.20                            | 2.200                         | 1.80                            | 2.800                         | 2.40                            | 3.400                         | 3.00                            | 4.000                         |
| 1.21                            | 2.210                         | 1.81                            | 2.810                         | 2.41                            | 3.410                         | 3.01                            | 4.010                         |
| 1.22                            | 2.220                         | 1.82                            | 2.820                         | 2.42                            | 3.420                         | 3.02                            | 4.020                         |
| 1.23                            | 2.230                         | 1.83                            | 2.830                         | 2.43                            | 3.430                         | 3.03                            | 4.030                         |
| 1.24                            | 2.240                         | 1.84                            | 2.840                         | 2.44                            | 3.440                         | 3.04                            | 4.040                         |
| 1.25                            | 2.250                         | 1.85                            | 2.850                         | 2.45                            | 3.450                         | 3.05                            | 4.050                         |
| 1.26                            | 2.260                         | 1.86                            | 2.860                         | 2.46                            | 3.460                         | 3.06                            | 4.060                         |
| 1.27                            | 2.270                         | 1.87                            | 2.870                         | 2.47                            | 3.470                         | 3.07                            | 4.070                         |
| 1.28                            | 2.280                         | 1.88                            | 2.880                         | 2.48                            | 3.480                         | 3.08                            | 4.080                         |
| 1.29                            | 2.290                         | 1.89                            | 2.890                         | 2.49                            | 3.490                         | 3.09                            | 4.090                         |
| 1.30                            | 2.300                         | 1.90                            | 2.900                         | 2.50                            | 3.500                         | 3.10                            | 4.100                         |
| 1.31                            | 2.310                         | 1.91                            | 2.910                         | 2.51                            | 3.510                         | 3.11                            | 4.110                         |
| 1.32                            | 2.320                         | 1.92                            | 2.920                         | 2.52                            | 3.520                         | 3.12                            | 4.120                         |
| 1.33                            | 2.330                         | 1.93                            | 2.930                         | 2.53                            | 3.530                         | 3.13                            | 4.130                         |
| 1.34                            | 2.340                         | 1.94                            | 2.940                         | 2.54                            | 3.540                         | 3.14                            | 4.140                         |

**EXHIBIT "B" CONTINUED**  
**ADJUSTMENT AUTHORIZATION**

TABLES OF DIFFERENTIALS FOR USE IN DETERMINING ADJUSTMENTS FOR  
DIFFERENCE IN SULFUR CONTENT OF PETROLEUM IN  
CARRIER SYSTEM COMMON STREAM PETROLEUM

| <u>PERCENT<br/>SULFUR</u> | <u>DIFF<br/>PER BBL</u> | <u>PERCENT<br/>SULFUR</u> | <u>DIFF<br/>PER BBL</u> |
|---------------------------|-------------------------|---------------------------|-------------------------|
| 3.15                      | 4.150                   | 3.75                      | 4.750                   |
| 3.16                      | 4.160                   | 3.76                      | 4.760                   |
| 3.17                      | 4.170                   | 3.77                      | 4.770                   |
| 3.18                      | 4.180                   | 3.78                      | 4.780                   |
| 3.19                      | 4.190                   | 3.79                      | 4.790                   |
| 3.20                      | 4.200                   | 3.80                      | 4.800                   |
| 3.21                      | 4.210                   | 3.81                      | 4.810                   |
| 3.22                      | 4.220                   | 3.82                      | 4.820                   |
| 3.23                      | 4.230                   | 3.83                      | 4.830                   |
| 3.24                      | 4.240                   | 3.84                      | 4.840                   |
| 3.25                      | 4.250                   | 3.85                      | 4.850                   |
| 3.26                      | 4.260                   | 3.86                      | 4.860                   |
| 3.27                      | 4.270                   | 3.87                      | 4.870                   |
| 3.28                      | 4.280                   | 3.88                      | 4.880                   |
| 3.29                      | 4.290                   | 3.89                      | 4.890                   |
| 3.30                      | 4.300                   | 3.90                      | 4.900                   |
| 3.31                      | 4.310                   | 3.91                      | 4.910                   |
| 3.32                      | 4.320                   | 3.92                      | 4.920                   |
| 3.33                      | 4.330                   | 3.93                      | 4.930                   |
| 3.34                      | 4.340                   | 3.94                      | 4.940                   |
| 3.35                      | 4.350                   | 3.95                      | 4.950                   |
| 3.36                      | 4.360                   | 3.96                      | 4.960                   |
| 3.37                      | 4.370                   | 3.97                      | 4.970                   |
| 3.38                      | 4.380                   | 3.98                      | 4.980                   |
| 3.39                      | 4.390                   | 3.99                      | 4.990                   |
| 3.40                      | 4.400                   | 4.00                      | 5.000                   |
| 3.41                      | 4.410                   |                           |                         |
| 3.42                      | 4.420                   |                           |                         |
| 3.43                      | 4.430                   |                           |                         |
| 3.44                      | 4.440                   |                           |                         |
| 3.45                      | 4.450                   |                           |                         |
| 3.46                      | 4.460                   |                           |                         |
| 3.47                      | 4.470                   |                           |                         |
| 3.48                      | 4.480                   |                           |                         |
| 3.49                      | 4.490                   |                           |                         |
| 3.50                      | 4.500                   |                           |                         |
| 3.51                      | 4.510                   |                           |                         |
| 3.52                      | 4.520                   |                           |                         |
| 3.53                      | 4.530                   |                           |                         |
| 3.54                      | 4.540                   |                           |                         |
| 3.55                      | 4.550                   |                           |                         |
| 3.56                      | 4.560                   |                           |                         |
| 3.57                      | 4.570                   |                           |                         |
| 3.58                      | 4.580                   |                           |                         |
| 3.59                      | 4.590                   |                           |                         |
| 3.60                      | 4.600                   |                           |                         |
| 3.61                      | 4.610                   |                           |                         |
| 3.62                      | 4.620                   |                           |                         |
| 3.63                      | 4.630                   |                           |                         |
| 3.64                      | 4.640                   |                           |                         |
| 3.65                      | 4.650                   |                           |                         |
| 3.66                      | 4.660                   |                           |                         |
| 3.67                      | 4.670                   |                           |                         |
| 3.68                      | 4.680                   |                           |                         |
| 3.69                      | 4.690                   |                           |                         |
| 3.70                      | 4.700                   |                           |                         |
| 3.71                      | 4.710                   |                           |                         |
| 3.72                      | 4.720                   |                           |                         |
| 3.73                      | 4.730                   |                           |                         |
| 3.74                      | 4.740                   |                           |                         |

For Sulfur Values above  
4.00%, the differential  
continues to increase  
0.01 /BBL per 0.01 Percent  
Sulfur

**EXHIBIT "C"**  
**ADJUSTMENT AUTHORIZATION**

RATIO FACTORS FOR SULFUR ADJUSTMENT  
WEIGHT OF PETROLEUM BY GRAVITY TO REFERENCE BASE OF 35.5° API GRAVITY  
CARRIER SYSTEM COMMON STREAM PETROLEUM

| <u>API GRAVITY</u> | <u>RATIO TO 35.5° WT.</u> | <u>API GRAVITY</u> | <u>RATIO TO 35.5° WT.</u> | <u>API GRAVITY</u> | <u>RATIO TO 35.5° WT.</u> | <u>API GRAVITY</u> | <u>RATIO TO 35.5° WT.</u> |
|--------------------|---------------------------|--------------------|---------------------------|--------------------|---------------------------|--------------------|---------------------------|
| 20.0               | 1.10248                   | 26.0               | 1.06038                   | 32.0               | 1.02140                   | 38.0               | 0.98526                   |
| 20.1               | 1.10177                   | 26.1               | 1.05967                   | 32.1               | 1.02084                   | 38.1               | 0.98469                   |
| 20.2               | 1.10106                   | 26.2               | 1.05911                   | 32.2               | 1.02013                   | 38.2               | 0.98412                   |
| 20.3               | 1.10021                   | 26.3               | 1.05840                   | 32.3               | 1.01956                   | 38.3               | 0.98356                   |
| 20.4               | 1.09950                   | 26.4               | 1.05769                   | 32.4               | 1.01899                   | 38.4               | 0.98285                   |
| 20.5               | 1.09880                   | 26.5               | 1.05698                   | 32.5               | 1.01828                   | 38.5               | 0.98228                   |
| 20.6               | 1.09809                   | 26.6               | 1.05641                   | 32.6               | 1.01772                   | 38.6               | 0.98172                   |
| 20.7               | 1.09738                   | 26.7               | 1.05571                   | 32.7               | 1.01715                   | 38.7               | 0.98115                   |
| 20.8               | 1.09667                   | 26.8               | 1.05500                   | 32.8               | 1.01644                   | 38.8               | 0.98058                   |
| 20.9               | 1.09596                   | 26.9               | 1.05443                   | 32.9               | 1.01588                   | 38.9               | 0.98001                   |
| 21.0               | 1.09525                   | 27.0               | 1.05372                   | 33.0               | 1.01517                   | 39.0               | 0.97945                   |
| 21.1               | 1.09454                   | 27.1               | 1.05301                   | 33.1               | 1.01460                   | 39.1               | 0.97888                   |
| 21.2               | 1.09383                   | 27.2               | 1.05245                   | 33.2               | 1.01403                   | 39.2               | 0.97831                   |
| 21.3               | 1.09313                   | 27.3               | 1.05174                   | 33.3               | 1.01332                   | 39.3               | 0.97775                   |
| 21.4               | 1.09242                   | 27.4               | 1.05103                   | 33.4               | 1.01276                   | 39.4               | 0.97718                   |
| 21.5               | 1.09171                   | 27.5               | 1.05046                   | 33.5               | 1.01219                   | 39.5               | 0.97661                   |
| 21.6               | 1.09086                   | 27.6               | 1.04975                   | 33.6               | 1.01148                   | 39.6               | 0.97605                   |
| 21.7               | 1.09015                   | 27.7               | 1.04904                   | 33.7               | 1.01091                   | 39.7               | 0.97548                   |
| 21.8               | 1.08944                   | 27.8               | 1.04848                   | 33.8               | 1.01035                   | 39.8               | 0.97491                   |
| 21.9               | 1.08873                   | 27.9               | 1.04777                   | 33.9               | 1.00964                   | 39.9               | 0.97434                   |
| 22.0               | 1.08802                   | 28.0               | 1.04706                   | 34.0               | 1.00907                   | 40.0               | 0.97378                   |
| 22.1               | 1.08731                   | 28.1               | 1.04649                   | 34.1               | 1.00850                   | 40.1               | 0.97321                   |
| 22.2               | 1.08661                   | 28.2               | 1.04578                   | 34.2               | 1.00780                   | 40.2               | 0.97264                   |
| 22.3               | 1.08590                   | 28.3               | 1.04507                   | 34.3               | 1.00723                   | 40.3               | 0.97208                   |
| 22.4               | 1.08519                   | 28.4               | 1.04451                   | 34.4               | 1.00666                   | 40.4               | 0.97151                   |
| 22.5               | 1.08448                   | 28.5               | 1.04380                   | 34.5               | 1.00609                   | 40.5               | 0.97094                   |
| 22.6               | 1.08377                   | 28.6               | 1.04323                   | 34.6               | 1.00539                   | 40.6               | 0.97038                   |
| 22.7               | 1.08320                   | 28.7               | 1.04252                   | 34.7               | 1.00482                   | 40.7               | 0.96981                   |
| 22.8               | 1.08249                   | 28.8               | 1.04181                   | 34.8               | 1.00425                   | 40.8               | 0.96924                   |
| 22.9               | 1.08179                   | 28.9               | 1.04125                   | 34.9               | 1.00369                   | 40.9               | 0.96867                   |
| 23.0               | 1.08108                   | 29.0               | 1.04054                   | 35.0               | 1.00298                   | 41.0               | 0.96811                   |
| 23.1               | 1.08037                   | 29.1               | 1.03997                   | 35.1               | 1.00241                   | 41.1               | 0.96754                   |
| 23.2               | 1.07966                   | 29.2               | 1.03926                   | 35.2               | 1.00184                   | 41.2               | 0.96697                   |
| 23.3               | 1.07895                   | 29.3               | 1.03855                   | 35.3               | 1.00128                   | 41.3               | 0.96641                   |
| 23.4               | 1.07824                   | 29.4               | 1.03799                   | 35.4               | 1.00057                   | 41.4               | 0.96584                   |
| 23.5               | 1.07753                   | 29.5               | 1.03728                   | 35.5               | 1.00000                   | 41.5               | 0.96527                   |
| 23.6               | 1.07682                   | 29.6               | 1.03671                   | 35.6               | 0.99943                   | 41.6               | 0.96471                   |
| 23.7               | 1.07612                   | 29.7               | 1.03600                   | 35.7               | 0.99887                   | 41.7               | 0.96414                   |
| 23.8               | 1.07541                   | 29.8               | 1.03544                   | 35.8               | 0.99816                   | 41.8               | 0.96357                   |
| 23.9               | 1.07470                   | 29.9               | 1.03473                   | 35.9               | 0.99759                   | 41.9               | 0.96300                   |
| 24.0               | 1.07413                   | 30.0               | 1.03416                   | 36.0               | 0.99702                   | 42.0               | 0.96244                   |
| 24.1               | 1.07342                   | 30.1               | 1.03345                   | 36.1               | 0.99646                   | 42.1               | 0.96187                   |
| 24.2               | 1.07271                   | 30.2               | 1.03288                   | 36.2               | 0.99589                   | 42.2               | 0.96145                   |
| 24.3               | 1.07201                   | 30.3               | 1.03218                   | 36.3               | 0.99518                   | 42.3               | 0.96088                   |
| 24.4               | 1.07130                   | 30.4               | 1.03161                   | 36.4               | 0.99461                   | 42.4               | 0.96031                   |
| 24.5               | 1.07059                   | 30.5               | 1.03090                   | 36.5               | 0.99405                   | 42.5               | 0.95974                   |
| 24.6               | 1.06988                   | 30.6               | 1.03033                   | 36.6               | 0.99348                   | 42.6               | 0.95918                   |
| 24.7               | 1.06931                   | 30.7               | 1.02962                   | 36.7               | 0.99291                   | 42.7               | 0.95861                   |
| 24.8               | 1.06860                   | 30.8               | 1.02906                   | 36.8               | 0.99220                   | 42.8               | 0.95804                   |
| 24.9               | 1.06790                   | 30.9               | 1.02835                   | 36.9               | 0.99164                   | 42.9               | 0.95748                   |
| 25.0               | 1.06719                   | 31.0               | 1.02778                   | 37.0               | 0.99107                   | 43.0               | 0.95691                   |
| 25.1               | 1.06648                   | 31.1               | 1.02707                   | 37.1               | 0.99050                   | 43.1               | 0.95648                   |
| 25.2               | 1.06577                   | 31.2               | 1.02651                   | 37.2               | 0.98994                   | 43.2               | 0.95592                   |
| 25.3               | 1.06520                   | 31.3               | 1.02580                   | 37.3               | 0.98937                   | 43.3               | 0.95535                   |
| 25.4               | 1.06449                   | 31.4               | 1.02523                   | 37.4               | 0.98880                   | 43.4               | 0.95478                   |
| 25.5               | 1.06378                   | 31.5               | 1.02452                   | 37.5               | 0.98809                   | 43.5               | 0.95422                   |
| 25.6               | 1.06308                   | 31.6               | 1.02395                   | 37.6               | 0.98753                   | 43.6               | 0.95365                   |
| 25.7               | 1.06237                   | 31.7               | 1.02339                   | 37.7               | 0.98696                   | 43.7               | 0.95308                   |
| 25.8               | 1.06180                   | 31.8               | 1.02268                   | 37.8               | 0.98639                   | 43.8               | 0.95266                   |
| 25.9               | 1.06109                   | 31.9               | 1.02211                   | 37.9               | 0.98583                   | 43.9               | 0.95209                   |



**EXHIBIT "C" CONTINUED**  
**ADJUSTMENT AUTHORIZATION**

RATIO FACTORS FOR SULFUR ADJUSTMENT  
WEIGHT OF PETROLEUM BY GRAVITY TO REFERENCE BASE OF 35.5° API GRAVITY  
CARRIER SYSTEM COMMON STREAM PETROLEUM

| <u>API</u><br><u>GRAVITY</u> | <u>RATIO TO</u><br><u>35.5° WT.</u> | <u>API</u><br><u>GRAVITY</u> | <u>RATIO TO</u><br><u>35.5° WT.</u> |
|------------------------------|-------------------------------------|------------------------------|-------------------------------------|
| 44.0                         | 0.95152                             | 50.0                         | 0.92006                             |
| 44.1                         | 0.95096                             | 50.1                         | 0.91949                             |
| 44.2                         | 0.95039                             | 50.2                         | 0.91892                             |
| 44.3                         | 0.94982                             | 50.3                         | 0.91850                             |
| 44.4                         | 0.94940                             | 50.4                         | 0.91793                             |
| 44.5                         | 0.94883                             | 50.5                         | 0.91751                             |
| 44.6                         | 0.94826                             | 50.6                         | 0.91694                             |
| 44.7                         | 0.94770                             | 50.7                         | 0.91651                             |
| 44.8                         | 0.94713                             | 50.8                         | 0.91595                             |
| 44.9                         | 0.94670                             | 50.9                         | 0.91552                             |
| 45.0                         | 0.94614                             | 51.0                         | 0.91495                             |
| 45.1                         | 0.94557                             | 51.1                         | 0.91439                             |
| 45.2                         | 0.94500                             | 51.2                         | 0.91396                             |
| 45.3                         | 0.94444                             | 51.3                         | 0.91339                             |
| 45.4                         | 0.94401                             | 51.4                         | 0.91297                             |
| 45.5                         | 0.94344                             | 51.5                         | 0.91240                             |
| 45.6                         | 0.94288                             | 51.6                         | 0.91198                             |
| 45.7                         | 0.94231                             | 51.7                         | 0.91141                             |
| 45.8                         | 0.94189                             | 51.8                         | 0.91099                             |
| 45.9                         | 0.94132                             | 51.9                         | 0.91042                             |
| 46.0                         | 0.94075                             | 52.0                         | 0.90999                             |
| 46.1                         | 0.94018                             | 52.1                         | 0.90943                             |
| 46.2                         | 0.93976                             | 52.2                         | 0.90900                             |
| 46.3                         | 0.93919                             | 52.3                         | 0.90843                             |
| 46.4                         | 0.93863                             | 52.4                         | 0.90801                             |
| 46.5                         | 0.93806                             | 52.5                         | 0.90744                             |
| 46.6                         | 0.93763                             | 52.6                         | 0.90702                             |
| 46.7                         | 0.93707                             | 52.7                         | 0.90645                             |
| 46.8                         | 0.93650                             | 52.8                         | 0.90602                             |
| 46.9                         | 0.93607                             | 52.9                         | 0.90546                             |
| 47.0                         | 0.93551                             | 53.0                         | 0.90503                             |
| 47.1                         | 0.93494                             | 53.1                         | 0.90446                             |
| 47.2                         | 0.93437                             | 53.2                         | 0.90404                             |
| 47.3                         | 0.93395                             | 53.3                         | 0.90361                             |
| 47.4                         | 0.93338                             | 53.4                         | 0.90305                             |
| 47.5                         | 0.93281                             | 53.5                         | 0.90262                             |
| 47.6                         | 0.93239                             | 53.6                         | 0.90206                             |
| 47.7                         | 0.93182                             | 53.7                         | 0.90163                             |
| 47.8                         | 0.93125                             | 53.8                         | 0.90106                             |
| 47.9                         | 0.93083                             | 53.9                         | 0.90064                             |
| 48.0                         | 0.93026                             | 54.0                         | 0.90007                             |
| 48.1                         | 0.92970                             | 54.1                         | 0.89965                             |
| 48.2                         | 0.92927                             | 54.2                         | 0.89922                             |
| 48.3                         | 0.92870                             | 54.3                         | 0.89865                             |
| 48.4                         | 0.92814                             | 54.4                         | 0.89823                             |
| 48.5                         | 0.92771                             | 54.5                         | 0.89766                             |
| 48.6                         | 0.92714                             | 54.6                         | 0.89724                             |
| 48.7                         | 0.92672                             | 54.7                         | 0.89681                             |
| 48.8                         | 0.92615                             | 54.8                         | 0.89624                             |
| 48.9                         | 0.92558                             | 54.9                         | 0.89582                             |
| 49.0                         | 0.92516                             | 55.0                         | 0.89525                             |
| 49.1                         | 0.92459                             |                              |                                     |
| 49.2                         | 0.92403                             |                              |                                     |
| 49.3                         | 0.92360                             |                              |                                     |
| 49.4                         | 0.92303                             |                              |                                     |
| 49.5                         | 0.92261                             |                              |                                     |
| 49.6                         | 0.92204                             |                              |                                     |
| 49.7                         | 0.92147                             |                              |                                     |
| 49.8                         | 0.92105                             |                              |                                     |
| 49.9                         | 0.92048                             |                              |                                     |

**EXHIBIT "D"**  
**SAMPLE QUALITY BANK CALCULATION**  
**CARRIER SYSTEM COMMON STREAM PETROLEUM**

**Receipt Bank**

| SHIPPER | BBLs          | %      | API  | FROM EXH. "C"      | %              | FROM EXH. "B" | FROM EXH. "A" | BBLs REC'D. x SULFUR | BBLs REC'D. x GRAV |
|---------|---------------|--------|------|--------------------|----------------|---------------|---------------|----------------------|--------------------|
|         | REC'D         | SULFUR | GRAV | RATIO TO 35.5° WT. | SULFUR x RATIO | SULFUR DIFF   | GRAVITY DIFF  | SULFUR DIFF          | GRAV DIFF          |
| A       | 100.00        | 0.92   | 29.8 | 1.03544            | 0.95           | 1.950         | 4.220         | 195.00               | 422.00             |
| B       | 150.00        | 0.36   | 38.6 | 0.98172            | 0.35           | 1.750         | 5.060         | 262.50               | 759.00             |
| C       | 100.00        | 0.42   | 36.4 | 0.99461            | 0.42           | 1.750         | 5.020         | 175.00               | 502.00             |
| C       | <u>200.00</u> | 0.78   | 46.2 | 0.93976            | 0.73           | 1.750         | 4.920         | <u>350.00</u>        | <u>984.00</u>      |
| TOTAL   | 550.00        |        |      |                    |                |               |               | 982.50               | 2667.00            |

Common stream weighted average GRAVITY value: 2667.00/550.0 = 4.84909

Common stream weighted average SULFUR value: 982.50/550.00 = 1.78636

**Shipper A:**

Weighted average GRAVITY value: 422.00/100 = 4.22000

Calculation: (4.84909 - 4.22000) x 100 = \$62.91

Weighted average SULFUR value: 195.00/100 = 1.95000

Calculation: (1.95000 - 1.78636) x 100 = \$16.36

**TOTAL Shipper A pays the bank:**

**\$79.27**

**Shipper B:**

Weighted average GRAVITY value: 759.00/150 = 5.06000

Calculation: (4.84909 - 5.06000) x 150 = (\$31.64)

Weighted average SULFUR value: 262.50/150 = 1.75000

Calculation: (1.75000 - 1.78636) x 150 = (\$5.45)

**TOTAL Shipper B receives from the bank:**

**(\$37.09)**

**Shipper C:**

Weighted average GRAVITY value: 1486.00/300 = 4.95333

Calculation: (4.84909 - 4.95333) x 300 = (\$31.27)

Weighted average SULFUR value: 525.00/300 = 1.75000

Calculation: (1.75000 - 1.78636) x 300 = (\$10.91)

**TOTAL Shipper C receives from the bank:**

**(\$42.18)**

**NET**

**\$0.00**

**Delivery Bank**

| SHIPPER | BBLs          | %      | API  | FROM EXH. "C"      | %              | FROM EXH. "B" | FROM EXH. "A" | BBLs REC'D. x SULFUR | BBLs REC'D. x GRAV |
|---------|---------------|--------|------|--------------------|----------------|---------------|---------------|----------------------|--------------------|
|         | REC'D         | SULFUR | GRAV | RATIO TO 35.5° WT. | SULFUR x RATIO | SULFUR DIFF   | GRAVITY DIFF  | SULFUR DIFF          | GRAV DIFF          |
| A       | 90.00         | 0.64   | 39.0 | 0.97945            | 0.63           | 1.750         | 5.080         | 157.50               | 457.20             |
| B       | 140.00        | 0.62   | 39.6 | 0.97605            | 0.61           | 1.750         | 5.080         | 245.00               | 711.20             |
| C       | 90.00         | 0.63   | 38.4 | 0.98285            | 0.62           | 1.750         | 5.060         | 157.50               | 455.40             |
| C       | <u>210.00</u> | 0.78   | 40.1 | 0.97321            | 0.76           | 1.760         | 5.100         | <u>369.60</u>        | <u>1071.00</u>     |
| TOTAL   | 530.00        |        |      |                    |                |               |               | 929.60               | 2694.80            |

Common stream weighted average GRAVITY value: 2694.80/530.0 = 5.08453

Common stream weighted average SULFUR value: 929.60/530.00 = 1.75396

**Shipper A:**

Weighted average GRAVITY value: 457.20/90 = 5.08000

Calculation: (5.08453 - 5.08000) x 90 = (\$0.41)

Weighted average SULFUR value: 157.50/90 = 1.75000

Calculation: (1.75000 - 1.75396) x 90 = \$0.36

**TOTAL Shipper A receives from the bank:**

**(\$0.05)**

**Shipper B:**

Weighted average GRAVITY value: 711.20/140 = 5.08000

Calculation: (5.08453 - 5.08000) x 140 = (\$0.63)

Weighted average SULFUR value: 245.00/140 = 1.75000

Calculation: (1.75000 - 1.75396) x 140 = \$0.55

**TOTAL Shipper B receives from the bank:**

**(\$0.08)**

**Shipper C:**

Weighted average GRAVITY value: 1526.40/300 = 5.08800

Calculation: (5.08453 - 5.08800) x 300 = \$1.04

Weighted average SULFUR value: 527.10/300 = 1.75700

Calculation: (1.75700 - 1.75396) x 300 = (\$0.91)

**TOTAL Shipper C pays the bank:**

**\$0.13**

**NET**

**\$0.00**